| TECHNICAL DATA SHEET | |
|---|---|
| Date of issue: 30.12.2026 | Version: 2.0 |

| | | |
|---|---|---|
| **Description** | ATM Paint Remover No. PR-600 is a ready-to-use paint stripper for water-based and solvent-based paints. It is formulated and designed for stripping paint and other coatings from various surface, providing deep penetration. Saving time and cost by easily lifting old paint films without damaging the original surface. | |
| **Application** | Using for paint stripper on multiple coating like alkyd enamel, lacquer, varnish, epoxy, polyurethane, etc. Usable on various surfaces such as wood, concrete, plaster, metal, and more. | |
| **Technical data** | Product type | Methylene Chloride Mixture |
| | Appearance | Cloudy white viscous liquid. |
| | Specific Gravity (water = 1) | 1.10 – 1.20 at 25 °C |
| | Viscosity (Ford cup No. 4) | C – D (Gardner bubble viscometers) at 25 °C |
| | Flash point | 24 - 25 °C (closed cup) |
| | Application tool | Brush, Roller, Trowel |
| | Time for remover at 25 °C | 20 – 25 minutes<br>(Stripping time may be longer than specified, depending on paint type, film thickness, and surface material.) |
| **Application Method** | • The surface should be clean and dry before proceeding.<br>• Apply ATM Paint Removal No. PR-600 onto the paint film.<br>• Leave for 20 – 25 minutes or until the paint film is blistered and stripped off from the substrate.<br>• Remove all stripped film thoroughly by using the trowel. Clean the surface with water or an appropriate solvent.<br>• Leave the surface completely dry before top coating or traffic. | |
| | **Precautions:**<br>• Contents are under pressure. Do not shake.<br>• Always by careful when unscrew the cap and cautiously open cap to avoid any accident from the pressure inside. | |

| | |
|---|---|
| **Theoretical Coverage** | 20 – 25 sq. m/ Litre/ Coat<br>(Depends on paint film type, thickness, surface condition, ana application tools). |
| **Storage & shelf life** | Best before in 3 years (sealed container). Keep in a cool dry and well-ventilated place.<br>Keep away from heat/ sparks/ open flames – no smoking.<br>Avoid direct to sunlight. Always keeps the container tightly closed when not in use and use again after correct storage. |
| **Safety, health & environment information** | Keep out of reach of children.<br>Volatile substance – Do not breathe mist, vapour or spray.<br>Use only outdoors or in a well-ventilated area.<br>Wear protective gloves, eye and face protection.<br>Avoid contact with skin or eyes.<br>Prolonged or repeated exposure may cause skin dryness or dermatitis.<br>If on skin, wash with plenty of soap and rinse skin with clean water.<br>If in eyes, rinse cautiously with water for several minutes.<br>If swallowed, immediately call a POISON CENTER/ doctor or physician.<br>Do NOT induce vomiting.<br>If the patient is loss of coordination or unconsciousness, transport to nearest facility for additional treatment.<br>Avoid release to the environment. |
| **Packing** | 0.3 kg/ 1 kg/ 3.5 kg |
| ***Disclaimer:*** | *The above information provided herein is based on the present state of our knowledge and practical experience. Since the product is often used under different conditions beyond our control. We cannot guarantee anything but the quality of the product itself. All the rights are reserved to change the data without any notice.* |