TECHNICAL DATA SHEET	
Date of issue: 03.10.2025	Version: 1.0

Description	BEAUTY MAX Semi-Gloss 2IN1 Acrylic Emulsion Paint, a superior product which developed and designed from 100% acrylic resin to provide a high-quality coating. Excellent adhesion. Long lasting protection against harsh weather conditions. Reduce UV Rays adsorption to coating surface. Dirt pickup resistance. High performance washability. Scrub resistance. Protect against fungus and algae. No added mercury and lead compounds. Environmentally-friendly and safety to both of resident and user. Certified for TIS-2321-2564: Weather Resistant Emulsion Paint (Exterior Paint category – using for Exterior and Interior decoration)	
Application	Suitable to use for decoration to both of walls and rooftiles, Exterior and Interior surfaces such as concrete, masonry, plaster, brick, and etc.	
Technical data	Product type	100% Acrylic Emulsion Paint
	Appearance	Viscous liquid in regards to product catalog.
	Texture	Semi-Gloss
	pH	8 - 10
	Specific Gravity (water = 1)	1.0 – 1.4 at 25 °C
	Solid content (% w/w)	34 – 38%
	Viscosity	95 – 100 KU at 25 °C
	Application	Brush, Roller or Spray gun
	Dilution	Dilute with clean water with ratio as following; • 5 – 10% for brush or roller • 10 – 15% for spray Mixed ratio can be varied to the desirable consistency and be compatible with application.
	Drying time at 25 °C	• Dry to touch ≤ 30 minutes • Dry to recoat ≤ 2 hours • Hard dry 7 days.

Paint System	Surface Preparation	
	New concrete surface	Allow the surface to be fully cured at least 30 days. Clean up to be free from dust, dirt, wax, oil, debris, and any contaminants. Leave to dry before service.
	Old concrete surface	≈ Previous paint layers that are chipping or peeling off should be removed thoroughly. Wipe off all contaminants from preparing surface. ≈ Imperfection parts, holes or cracks should be fixed with patching compounds. Cracks width < 1 mm and discontinuous, fixed with ATM Wall Putty No. 107 while cracks width > 1 mm and discontinuous, fixed with ATM Sealant. ≈ If mildew or algae are presented, remove thoroughly. ≈ Clean the surface with clean water and allow to dry.
	Priming	
	New concrete surface	Apply with BEAUTY MAX 2IN1 Primer (Water-based) for 1 coat.
	Old concrete surface	Apply with BEAUTY MAX 3IN1 Primer (Solvent-based) for 1 coat.
	Top Coating	
	Apply **BEAUTY MAX Semi-Gloss 2IN1 Acrylic Emulsion Paint** for 2-3 coats with drying time to recoat is 2 hours by approximately.	
Theoretical Coverage	8 - 10 sq.m/ Litre/ coat (By practical terms, the coverage may be varied from a surface conditions, application method and a dilution).	

Storage & shelf life	Best before in 5 years (sealed container). Keep in a well-ventilated place. Avoid direct to sunlight. Always keeps the container tightly closed when not in use and use again after correct storage.
Safety, health & environment information	Keep out of reach of children. Use in a well-ventilated area. Avoid contact with skin or eyes. Prolonged or repeated exposure may cause skin dryness or dermatitis. If on skin, wash with plenty of soap and rinse skin with clean water. If in eyes, rinse cautiously with water for several minutes. Do not use empty container for food stuff. Do not empty into drains.
Packing	1 gallon / 2.5 gallon
Disclaimer:	*The above information provided herein is based on the present state of our knowledge and practical experience. Since the product is often used under different conditions beyond our control. We cannot guarantee anything but the quality of the product itself. All the rights are reserved to change the data without any notice.*