

ATM Wood Finish Paint

Version: 1.0

Date of Issue: 25.04.2018

1. IDENTIFICATION OF THE SUBSTANCE OR MIXTURE AND OF THE SUPPLIER

Material name : ATM Wood Finish Paint (for all colours)

Recommended use : Suitable to apply on wood piece, wood plank or fibre cement. Including to concrete

or masonry. It can be applied to both of Interior and Exterior.

Supplier : U.R. Chemical Co., Ltd.

81, Moo 11, Tambol Bang-pla, Amphur Bang-plee

Samutprakan 10540 ,Thailand

Telephone : +66 2 312 1415-9

Fax : +66 2 312 1048

Emergency Telephone number : +66 2 312 1415

2. HAZARD IDENTIFICATION

GHS Classification : Not Classified by according to GHS criteria.

GHS Label Elements

Symbol(s) : No sign.

Signal words : -

GHS Hazard Statement :

Physical hazards : Not classified as physical hazardous according to GHS criteria.

Health hazards : Not classified as health hazardous according to GHS criteria.

Environmental hazards : Not classified as environmental hazardous according to GHS criteria.

GHS Precautionary

Statement

 Prevention
 : N/A

 Response
 : N/A

 Storage
 : N/A

Disposal : - P501: Dispose of contents/ container to appropriate waste reclaimer in

accordance with local and national regulations.

3. COMPOSITION/ INFORMATION ON INGREDIENTS

Components

Chemical Identity	CAS No.	% w/w
Binder	Proprietary	40 – 50%



ATM Wood Finish Paint

Version: 1.0

Date of Issue: 25.04.2018

H₂O	7732-18-5	25 – 30%
Extender	Proprietary	8 – 15%
Additives	Proprietary	1.8 – 2.6%
Pigments	Proprietary	Variable depends on colour code.

4. FIRST-AID MEASURES

Inhalation Remove to fresh air, if rapid recovery does not occur, transport to nearest

medical facility for additional treatment.

Skin contact Remove contaminated clothing. In a shower, wash affected area with soap and

water at least 15 minutes. Seek medical attention if irritant occurs or persists.

Wash clothing before reuse.

Eye contact Remove contact lenses, if present. Immediately flush eyes with plenty of clean

> running water at least 15 minutes while holding eyelids open. If eye irritation, burning sensation, redness, swelling and/ or blurred vision. Transport to the

nearest medical facility for additional treatment.

Ingestion If swallowed, do not induce vomiting, transport to the nearest medical facility for

additional treatment. If vomiting occurs spontaneously, keep head below hips to

prevent aspiration.

5. FIRE FIGHTING MEASURES

Suitable extinguishing media Foam, water spray or fog. Dry chemical powder, carbon dioxide

Unsuitable extinguishing No data.

Specific hazard arising

from chemicals

Protective equipment & precautions for fire fighters

Typically, this product is non-flammable but when incomplete combustion occurs or the evaporation of water in open flames, Carbon monoxide may be evolved.

Wear protective clothing and self-contained breathing apparatus.

Additional advice Keep adjacent containers cool by spraying with water.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, Protective equipment and **Emergency procedures**

Environmental precautions

Method and material

Avoid contact with eyes, skin and clothing by using the suitable protective

equipment as required.

Use appropriate containment (of product and firefighting water) to avoid

environmental contamination. Prevent from spreading or entering drains, ditches

or rivers by using sand, earth, or other appropriate barriers.

Authorities should be notified if reportable quantity release occurs.

For small liquid spills (< 1 drum): transfer by mechanical means to a labelled, for containment and

sealable container for product recovery or safe disposal.



ATM Wood Finish Paint

Version: 1.0

Date of Issue: 25.04.2018

clean up

For large liquid spills (> 1 drum): Perform with same method for small liquid spills. Retain as contaminated waste. Recover or recycle if possible.

7. HANDLING AND STORAGE

Precautions for safe handling : Avoid contact with skin or eyes and clothing. Repeated or long time exposure

may cause skin dryness and dermal disease. Keep container closed when not in use.

Conditions for safe storage/ Including any incompatability The container should be labelled and keep tightly closed. Keep in a well-

ventilated place. Avoid store near incompatible materials such as oxidizing

agent. Keep cool.

Storage temperature: Ambient

Recommended materials Unsuitable materials Container advice The recommended container of this product is plastic or Tin by inside should be coating with Phenolic. Steel container or Tin container without Phenolic coating

should be avoided.

8. EXPOSURE CONTROL/ PERSONAL PROTECTION

Threshold limit for exposure control

Occupation exposure limits : No data.

Appropriate engineering control : Select controls based on a risk assessment of local circumstances. Appropriate

measures include: Use sealed systems as far as possible. Adequate ventilation to

control airborne concentrations below the exposure guidelines/limits are

recommended.

Individual protection measures

Respiratory protection : By working under a well-ventilated area, the respiratory equipment can be skipped

to use during operation.

Hand protection : Using gloves constructed of chemical resistant materials such as heavy nitrile

rubber if frequent or prolonged contact is expected.

Neoprene or PVC gloves also be using in case of incidential contact or splash

protection.

Gloves must only be worn on clean hands. After using gloves, hands should be

washed and dried thoroughly.

Eye protection : Chemical splash goggles (chemical monogoggles). Eye washes and showers for

emergency use are recommended to the work area.

Protective clothing : Protective gloves, safety shoes and boots are recommended.

Remarks : Personal protective equipment is not considered to long term solution of exposure

control.

9. PHYSICAL AND CHEMICAL PROPERTIES



ATM Wood Finish Paint

Version: 1.0

Date of Issue: 25.04.2018

Appearance : Viscous liquid by colours refers to Catalogue of ATM Wood stain (water based).

Odor : Odourless.

Initial Boiling Point : No data

Melting Point : No data

Viscosity : 100 – 105 KU @ 25° C

Specific Gravity (water = 1) : 1.10 - 1.15 @ 25° C

pH : 8.5 – 9.5 **% Non-Volatile** : 40 - 45

Water solubility : Soluble

10. STABILITY AND RELIABILITY

Chemical stability : Stable under normal conditions of use.

Possibility of hazardous reaction : No data

Condition to avoid : Avoid using under high temperature condition. Avoid direct to sunlight.

Incompatible materials : No data.

Hazardous decomposition

products

Carbon dioxide, carbon monoxide.

11. TOXICOLOGICAL INFORMATION

Basis of assessment : Information given is based on product data, mixtures of product and/ or the

similar product and/ or ingredients.

Acute oral toxicity : Expected to be low toxicity.

Acute dermal toxicity : Expected to be Low toxicity.

Acute inhalation toxicity : Expected to be low of toxicity if inhaled.

Skin corrosion/ irritation : Slightly irritation to skin.

Sensitisaton: No data.Serious eye damage/ irritation: No dataRespiratory tract irritation: No dataAspiration hazard: No dataGerm cell mutagenicity: No data

Carcinogenicity : No data



Safety Data Sheet ATM Wood Finish Paint

Version: 1.0

Date of Issue: 25.04.2018

12. ECOLOGICAL INFORMATION

Basis for Assessment The information given below is based partly on a knowledge of the components

and the ecotoxicology of similar products.

Acute Toxicity : No data

Mobility : This product is completely miscible and can spread around in water.

Persistence/degradability : No data.

Bioaccumulative potential : Does not bioaccumulate significantly.

13. DISPOSAL CONSIDERATION

Material disposal : Recover or recycle if possible. It is responsibility of the waste generator to

determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses. Waste product should not be allowed to contaminate soil or

water.

Container disposal : Disposal should be in accordance with applicable regional, national, and local

laws and regulations. Send a disposal container to drum recover or metal

reclaimer.

14. TRANSPORT INFORMATION

ADR /RID : Classified as NON-DANGEROUS GOODS by the criteria of UNRTDG

IMDG : Classified as NON-DANGEROUS GOODS by the criteria of IMDG

IATA : Classified as NON-DANGEROUS GOODS by the criteria of IATA

15. REGULATORY INFORMATION

- Notification of the Ministry of Industry subject to Globally Harmonized System of Classification and Labelling of Chemicals (GHS) B.E. 2555 (2012)



ATM Wood Finish Paint

Version: 1.0

Date of Issue: 25.04.2018

16. OTHER INFORMATION

SDS version : 1.0

Date of Issue : 25.04.2018

Reference :

Disclaimer : This information is based on our current knowledge and is intended to

describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be constructed as guaranteeing any

specific property of the product.

All rights reserved to inform the precise quantity of constituents in the product. By reason is confidential of the company which could not reveal or propagate

to the public.