

ATM Roof Paint

Version: 1.0

Date of Issue: 20.09.2021

1. IDENTIFICATION OF THE SUBSTANCE OR MIXTURE AND OF THE SUPPLIER

Material name : ATM Roof Paint

Recommended use : An idealized to use as roof finish for variety of roof tiles, flat sheet and fiber cement board.

Supplier : U.R. Chemical Company Limited.

81 Moo 11 Soi Thanasit 4, Bang Pla, Bang Phli District, Samut Prakan 10540, Thailand

Telephone : (+662) 312 1415-9

Fax : (+662) 312 1048

Emergency Telephone number : (+662) 312 1415

2. HAZARD IDENTIFICATION

GHS Classification : - Skin Irritation Category 3

Skin Sensitization Category 1
 Carcinogenicity Category 2
 Acute Aquatic Category 3

GHS Label Elements

Symbol (s)





Signal words : Warning

GHS Hazard Statement

Physical Hazard : Not identified

Health Hazard : - H315 Causes skin irritation

- H317 May causes an allergic skin reaction

- H351 Suspected of causing cancer

Environmental Hazard : - H402 Harmful to aquatic life



ATM Roof Paint

Version: 1.0

Date of Issue: 20.09.2021

GHS Precautionary

Prevention : - P203 Obtain, read and follow all safety instructions before use.

- P261 Avoid breating dust/fume/gas/mist/vapours/spray.

- P272 Contaminated work clothing should not be allowed out of the workplace.

- P281 Wear protective gloves / protective clothing / eye protection / face

protection / hearing protection.

P273 Avoid release to environment.

Response : - P332+P333+P317 If skin or eye irritation persists: Get medical help.

- P302+P352 IF ON SKIN: Wash with plenty of water.

- P318 IF exposed or concerned, get medical advice.

P362+ P364 Take off contaminated clothing and wash it before reuse.

Storage : - P405 Store locked up.

Disposal : - P501 Dispose of contents / container to accordance with local / regional

/international regulation (to be specified).

3. COMPOSITION/ INFORMATION ON INGREDIENTS

Hazardous components

Components 2-Amino-2-Methyl-1-Propanol	CAS No.	% w/w 0.1-0.5%	Hazard Class		
			- Skin Irritation Category	2	
			- Eye Irritation Category	2	
			- Chronic Aquatic Category	3	
Biocide 1	Proprietary	0.1-0.5%	- Acute tox. Inhale Category	4	
			- Skin corrosion Category	1B	
			- Serious eye damage Category	1	
			- Skin sensitization Category	1	
			- Short-term (acute) aquatic Category	1	
			- Long-term (chronic) aquatic, Category	2	
Biocide 2	Proprietary	0.1-0.5%	- Skin sensitization, Category	1	
			- Carcinogenicity Category	2	
			- Long-term (chronic) aquatic Category	3	
Pigment	Proprietary	15-25%	Not Classified		
Water	7732-18-5	20-25%	Not Classified		
Binder	Proprietary	50-60%	Not Classified		
Extender	Proprietary	5-10%	Not Classified		
Additives	Proprietary	1-5%	Not Classified		
Others	Proprietary	1-5%	Not Classified		



ATM Roof Paint

Version: 1.0

Date of Issue: 20.09.2021

4. FIRST-AID MEASURES

Inhalation : Remove to fresh air, if rapid recovery does not occur, transport to nearest medical facility

for additional treatment.

Skin contact : Remove contaminated clothing. In a shower, wash affected area with soap and water

at least 15 minutes. Seek medical attention if irritant occurs or persists. Wash clothing

before reuse.

Eye contact : Remove contact lenses, if present. Immediately flush eyes with plenty of clean running

water at least 15 minutes while holding eyelids open. If eye irritation, burning sensation, redness, swelling and/ or blurred vision. Transport to the nearest medical facility for

additional treatment.

Ingestion : If swallowed, do not induce vomiting, transport to the nearest medical facility for additional

treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

5. FIRE FIGHTING MEASURES

Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon dioxide

Unsuitable extinguishing : Not available

Specific hazard arising from

chemicals

: Typically, this product is non-flammable but when incomplete combustion occurs or the

evaporation of water in open flames, Carbon monoxide may be evolved.

Protective equipment & precautions

for fire fighters

Wear protective clothing and self-contained breathing apparatus.

Additional advice : Keep adjacent containers cool by spraying with water.

required.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, Protective equipment and Emergency procedures Avoid contact with eyes, skin and clothing by using the suitable protective equipment as

Environmental precautions

: Use appropriate containment (of product and firefighting water) to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand,

earth, or other appropriate barriers.

Authorities should be notified if reportable quantity release occurs.



ATM Roof Paint

Version: 1.0

Date of Issue: 20.09.2021

Method and material for containment and clean up

: For small liquid spills (< 1 drum): transfer by mechanical means to a labelled, sealable container for product recovery or safe disposal.

For large liquid spills (> 1 drum): Perform with same method for small liquid spills. Retain as contaminated waste. Recover or recycle if possible.

7. HANDLING AND STORAGE

Precautions for safe handling

: Avoid contact with skin or eyes and clothing

Keep container closed when not in use.

Conditions for safe storage/ Including any incompatibility

: The container should be labelled and keep tightly closed. Keep in a well-ventilated place.

Avoid store near incompatible materials such as oxidizing agent. Keep cool.

Storage temperature: Ambient

Recommended materials Unsuitable materials Container advice

: No special requirement for material container.

8. EXPOSURE CONTROL/ PERSONAL PROTECTION

Threshold limit for exposure control

Occupation exposure limits

Commonanta	ACGIH	Domorko	
Components	TWA	STEL	—— Remarks
Ethylene Glycol	29 mg/m³	-	
Distillates (Petroleum)	5 mg/m ³	-	

Appropriate engineering control

Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Use sealed systems as far as possible. Adequate ventilation to control airborne concentrations
below the exposure guidelines/limits are recommended.

Individual protection measures

Respiratory protection

Working under a well-ventilated area, use the respiratory equipment during operation.

Hand protection

Using gloves constructed of chemical resistant materials such as heavy nitrile rubber if frequent or prolonged contact is expected.

Neoprene or PVC gloves also be using in case of incidential contact or splash protection.

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried

thoroughly.



ATM Roof Paint

Version: 1.0

Date of Issue: 20.09.2021

Eye protection : Chemical splash goggles (chemical monogoggles). Eye washes and showers for emergency use

are recommended to the work area.

Protective clothing . Protective gloves, safety shoes and boots are recommended.

Remark: Personal protective equipment is not considered to long term solution of exposure control.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Colour viscous liquid regarding to catalog

Odor : Mild odor

pH : 8-10

Initial Boiling Point : Not available

Melting Point : Not available

Flash point : Not combustible

Viscosity : 100-105 KU at 25 °C

Specific Gravity (water = 1) : 1.300 - 1.400 at 25 °C

Water solubility : Excellent solubility

10. STABILITY AND RELIABILITY

Chemical stability : Stable under normal conditions of use.

Possibility of hazardous reaction : Not available

Condition to avoid . Avoid using under high temperature condition. Avoid direct to sunlight.

Incompatible materials: Strong oxidizing, strong acid and strong base.

Hazardous decomposition

products

products

11. TOXICOLOGICAL INFORMATION

Basis of assessment : Information given is based on product data, mixtures of product and/ or the similar

Carbon monoxide, Carbon dioxide and Nitrogen oxide.

product and/ or ingredients.

Acute oral toxicity : The classification criteria are not met based on raw material data.

Acute dermal toxicity : Not available based on raw material data.

Acute inhalation toxicity : The classification criteria are not met, based on raw material data.

Skin corrosion/ irritation : Cause mild skin irritation.

Sensitization : May cause an allergic skin reaction.

Serious eye damage/ irritation : The classification criteria are not met, based on raw material data.



ATM Roof Paint

Version: 1.0

Date of Issue: 20.09.2021

Respiratory tract irritation : Not available based on raw material data.

Aspiration hazard : Not available based on raw material data.

Germ cell mutagenicity : Not available based on raw material data.

Carcinogenicity : Suspected of causing cancer

Reproductive toxicity: Not available based on raw material data.

Specific target organ toxicity-Single

exposure

Not available based on raw material data.

Specific target organ toxicity-

Repeated exposure

Not available based on raw material data.

12. ECOLOGICAL INFORMATION

Basis for Assessment : The information given below is based partly on a knowledge of the components and

the ecotoxicology of similar products.

Acute Toxicity : Harmful to aquatic life

Components	Species	Value
1,2-benzisothiazol-3(2H)-one	Toxicity to fish	LC ₅₀ (Oncorhynchus mykiss): 2.18 ppm
		Exposure time 96 hr.
	Toxicity to daphnia	EC ₅₀ (Daphnia magna): 2.94 ppm
		Exposure time 48 hr.
	Toxicity to algae	ErC ₅₀ (Green algae): 0.11
		Exposure time 72 hr.
2-methyl-2H-isothiazol-3-one (MIT)	Toxicity to fish	LC ₅₀ (Oncorhynchus mykiss): 4.77 ppm
		Exposure time 96 hr.
	Toxicity to daphnia	$\mathrm{EC}_{50}(\mathrm{daphnia\ magna})$: 0.93-1.9 ppm
		Exposure time 48 hr.
	Toxicity to alga	ErC ₅₀ (Green algae): 0.158
		Exposure time 72 hr.
N-(3-aminopropyl) -N-dodecylpropane-1,3-	Toxicity to fish	LC_{50} (Lipomas macro chirus): 0.45 ppm
diamine (Diamine)		Exposure time 96 hr.
	Toxicity to daphnia	EC ₅₀ (daphnia magna): 0.073 ppm
		Exposure time 48 hr.
	Toxicity to alga	ErC ₅₀ (Green algae): 0.012
		Exposure time 72 hr.

Mobility : This product is completely miscible and can spread around in water.

Persistence/degradability : Not available

Bioaccumulative potential : Does not bioaccumulate significantly.



ATM Roof Paint

Version: 1.0

Date of Issue: 20.09.2021

13. DISPOSAL CONSIDERATION

Material disposal : Recover or recycle if possible. It is responsibility of the waste generator

to determine the toxicity and physical properties of the material generated

to determine the proper waste classification and disposal methods in compliance

with applicable regulations. Do not dispose into the environment, in drains or in

water courses. Waste product should not be allowed to contaminate soil or water.

Container disposal : Disposal should be in accordance with applicable regional, national, and local laws

and regulations. Send a disposal container to drum recover or metal reclaimer.

14. TRANSPORT INFORMATION

ADR /RID : Classified as NON-DANGEROUS GOODS by the criteria of UNRTDG

IMDG : Classified as NON-DANGEROUS GOODS by the criteria of IMDG

IATA : Classified as NON-DANGEROUS GOODS by the criteria of IATA

15. REGULATORY INFORMATION

Notification of the Ministry of Industry subject to Globally Harmonized System of Classification and Labelling of Chemicals (GHS) B.E. 2019

16. OTHER INFORMATION

SDS version : 1.0

Date of Issue : 20.09.2021

Reference

Disclaimer : This information is based on our current knowledge and is intended to describe the

product for the purposes of health, safety and environmental requirements only.

It should not therefore be constructed as guaranteeing any specific property of the

product.

All rights reserved to inform the precise quantity of constituents in the product.

By reason is confidential of the company which could not reveal or propagate to the

public.