

**SAFETY DATA SHEET**


Date of Issue: 30.08.2023

Version: 2.0

**1. IDENTIFICATION OF THE SUBSTANCE OR MIXTURE AND OF THE SUPPLIER**

<b>Material name</b>	ATM Thinner AAA 100% No. T75
<b>Recommended use</b>	For tools cleaning e.g. brush, spray gun.
<b>Supplier</b>	UR Chemical Co., Ltd.
<b>Address</b>	81, Moo 11, Tambol Bang-pla, Amphur Bang-plee, Samutprakan 10540
<b>Telephone</b>	+66 2 312 1415-9
<b>Fax</b>	+66 2 312 1048
<b>Emergency Telephone number</b>	+66 2 312 1415

**2. HAZARDS IDENTIFICATION**

<b>GHS Classification</b>	1. Flammable liquids 2. Skin corrosion/ irritation 3. Serious eye damage/ irritation 4. Toxic to reproduction 5. STOT (single exposure) 6. STOT (repeated exposure) 7. Aspiration hazards	category 2 category 2 category 2A category 2 category 3 category 2 category 1
<b>GHS Label Elements</b>		
Symbol(s)		
Signal words	<b>DANGER</b>	
<b>GHS Hazard Statement</b>		
Physical hazards	H225: Highly flammable liquid and vapour.	
Health hazards	H315: Causes skin irritation. H319: Causes serious eye irritation. H361: Suspected of damaging fertility or the unborn child. H336: May cause drowsiness or dizziness.	

**SAFETY DATA SHEET**

Date of Issue: 30.08.2023

Version: 2.0

	<p>H373: May cause damage to organs through prolonged or repeated exposure.</p> <p>H304: May be fatal if swallowed and enters airways.</p>
Environmental hazards	Not classified as environmental hazard under GHS criteria.
<b>GHS Precautionary Statement</b>	
Prevention	<ul style="list-style-type: none"> <li>- P210: Keep away from heat/ sparks/ open flames/ hot surfaces. – no smoking.</li> <li>- P240: Ground/ bond container and receiving equipment.</li> <li>- P241: Use explosion-proof electrical/ ventilating/ lighting equipment.</li> <li>- P242: Use only non-sparking tools.</li> <li>- P243: Take precautionary measures against static discharge.</li> <li>- P201: Obtain special instruction before use.</li> <li>- P202: Do not handle until all safety precautions have been read and understood.</li> <li>- P260: Do not breathe mist/ vapours.</li> <li>- P271: Use only outdoors or in a well-ventilated area.</li> <li>- P264: Wash hands and contaminated body parts thoroughly after handling.</li> <li>- P280: Wear protective gloves, eyes and face protection equipment.</li> <li>- P273: Avoid release to the environment.</li> </ul>
Response	<ul style="list-style-type: none"> <li>- P303+P361+P353: IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.</li> <li>- P332+P313: If skin irritation occurs: Get medical advice/ attention.</li> <li>- P362: Take off contaminated clothing and wash before reuse.</li> <li>- P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.</li> <li>- P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.</li> <li>- P331: Do NOT induce vomiting.</li> <li>- P308+P313: IF exposed or concerned: Get medical advice/ attention.</li> <li>- P314: Get medical advice/ attention if you feel unwell.</li> <li>- P370+P378: In case of fire: Use appropriated media for extinction.</li> </ul>
Storage	<ul style="list-style-type: none"> <li>- P403+P235: Store in a well-ventilated place. Keep cool.</li> <li>- P233: Keep container tightly closed.</li> <li>- P405: Store locked up.</li> </ul>
Disposal	<ul style="list-style-type: none"> <li>- P501: Dispose of contents/ container to appropriate waste reclaimer in accordance with local and national regulations.</li> </ul>

**SAFETY DATA SHEET**

Date of Issue: 30.08.2023

Version: 2.0

**3. COMPOSITION/ INFORMATION ON INGREDIENTS**
**HAZARD IDENTIFICATION**

Chemical Identity	CAS No.	% w/w	Hazard category
Toluene	108-88-3	> 50%	<ul style="list-style-type: none"> <li>- H225: Flammable liquids, cat. 2</li> <li>- H315: Skin corrosion/ irritation, cat. 2</li> <li>- H361: Reproductive toxicity, cat. 2</li> <li>- H336: STOT (Single Exposure), cat. 3</li> <li>- H373: STOT (Repeated Exposure), cat. 2</li> <li>- H304: Aspiration hazard, cat. 1</li> </ul>
Acetone	67-64-1	> 5%	<ul style="list-style-type: none"> <li>- H225: Flammable liquids, cat. 2</li> <li>- H320: Serious eye damage/ irritation, cat. 2B</li> <li>- H336: STOT (single exposure), cat. 3</li> <li>- H305: Aspiration hazard, cat. 2</li> </ul>
Isopropanol	67-63-0	> 5%	<ul style="list-style-type: none"> <li>- H225: Flammable liquids, cat. 2</li> <li>- H303: Acute toxicity (oral), cat. 5</li> <li>- H319: Serious eye damage/ irritation, cat. 2A</li> <li>- H336: STOT (single exposure), cat. 3</li> <li>- H305: Aspiration hazard, cat. 2</li> </ul>
Butyl Glycol Ether	111-76-2	> 0.1%	<ul style="list-style-type: none"> <li>- H227: Flammable liquids, cat. 4</li> <li>- H302: Acute toxicity (oral), cat. 4</li> <li>- H312: Acute toxicity (dermal), cat. 4</li> <li>- H332: Acute toxicity (inhalation), cat. 4</li> <li>- H315: Skin corrosion/ irritation, cat. 2</li> <li>- H319: Serious eye damage/ irritation, cat. 2A</li> </ul>
Methyl Ethyl Ketone	78-93-3	> 0.1%	<ul style="list-style-type: none"> <li>- H225: Flammable liquids, cat. 2</li> <li>- H303: Acute toxicity (oral), cat. 5</li> <li>- H333: Acute toxicity (inhalation), cat. 5</li> <li>- H316: Skin corrosion/ irritation, cat. 3</li> <li>- H319: Serious eye damage/ irritation, cat. 2A</li> <li>- H336: STOT (single exposure), cat. 3</li> <li>- H305: Aspiration hazard, cat. 2</li> </ul>

**Note:** All rights reserved to inform the precise quantity of constituents in the product. By reason is confidential of the company which could not reveal or propagate to the public.

**SAFETY DATA SHEET**

Date of Issue: 30.08.2023

Version: 2.0

**4. FIRST-AID MEASURES**

<b>Inhalation</b>	Remove to fresh air, if rapid recovery does not occur, transport to nearest medical facility for additional treatment.
<b>Skin contact</b>	Remove contaminated clothing. In a shower, wash affected area with soap and water at least 15 minutes. Seek medical attention if irritant occurs or persists. Wash clothing before reuse.
<b>Eye contact</b>	Remove contact lenses, if present. Immediately flush eyes with plenty of clean running water at least 15 minutes while holding eyelids open. If eye irritation, burning sensation, redness, swelling and/ or blurred vision. Transport to the nearest medical facility for additional treatment.
<b>Ingestion</b>	If swallowed, do not induce vomiting, transport to the nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101 °F (38.3 °C), shortness of breath, chest congestion or continued coughing or wheezing. If vomiting occurs spontaneously keep head below hips to prevent aspiration. Give nothing by mouth. Do not induce vomiting.
<b>Most important Symptom/ Effect, Acute &amp; Delayed</b>	Skin irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blisters. Breathing of high concentration vapors may cause central nervous system (CNS) depression resulting in dizziness, lightheadedness, headache, nausea, lightheadedness, headache, nausea and loss of coordination. Respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, coughing, and/ or difficulty breathing. If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty breathing, chest congestion, shortness of breath, and/ or fever.

**5. FIRE FIGHTING MEASURES**

<b>Suitable extinguishing media</b>	Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only. Do not discharge extinguishing waters into the aquatic environment.
-------------------------------------	--

**SAFETY DATA SHEET**

Date of Issue: 30.08.2023

Version: 2.0

<b>Unsuitable extinguishing</b>	Do not use water in a jet.
<b>Specific hazard arising from chemicals</b>	The combustion can emit the irritating and toxic vapors/ fumes as carbon monoxide, carbon dioxide. The vapor is heavier than air, spreads along the ground and distant ignition is possible.
<b>Protective equipment &amp; precautions for fire fighters</b>	Wear full protective clothing and self-contained breathing apparatus.
<b>Additional advice</b>	Keep adjacent containers cool by spraying with water.

**6. ACCIDENTAL RELEASE MEASURES**

<b>Personal precautions, Protective equipment and Emergency procedures</b>	Isolate hazard area and deny entry to unnecessary or unprotected personnel. Step up wind and keep out of low areas. Avoid contact with spilled or released material. Immediately take off contaminated clothing. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding all equipments. Monitor area with combustible indicator. Wear full protective clothing and self-contained breathing apparatus.
<b>Environmental precautions</b>	Shut off leaks, if possible, without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment (of product and firefighting water) to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding all equipment.
<b>Method and material for containment and clean up</b>	For small liquid spills (< 1 drum): transfer by mechanical means to a labelled, sealable container for product recovery or safe disposal. Allow residue to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.  For large liquid spills (> 1 drum): Perform with same method for small liquid spills. Do not flush away residues with water. Retain as contaminated waste. Allow residue to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.
<b>Additional advice</b>	Authorities should be notified if any exposure to the general public or the environment occurs or is likely to occur. Vapour may form an explosive mixture with air.

**SAFETY DATA SHEET**

Date of Issue: 30.08.2023

Version: 2.0

**7. HANDLING AND STORAGE**
**Precautions for safe handling**

Avoid inhale vapour and/or mist. Avoid contact with skin, eye and clothing. Only use in a well-ventilated area. Wash thoroughly after handling. Do not smoke. Remove ignition sources. Avoid sparks. Keep container closed when not in use. The vapour is heavier than air, spreads along the ground and distant ignition is possible. Handle and open container with care in a well-ventilated area. Do not empty into drain.

Handling temperature: Ambient.

**Conditions for safe storage/  
Including any incompatibility**

Keep away from aerosol, flammables, incompatible materials such as oxidizing agent, corrosive and other flammable products. The container should be labelled and keep tightly closed. Keep in a well-ventilated place, away from sunlight. Keep cool.

Storage temperature: Ambient

**Recommended materials**
**Unsuitable materials**
**Container advice**

For container, use mild steel or stainless steel. Avoid prolonged contact with natural, butyl or nitrile rubbers. Containers, even those that have been emptied can contain explosive vapours. Do not cut, drill, grind, weld or perform similar operation on or near containers.

**8. EXPOSURE CONTROL/ PERSONAL PROTECTION**
**Threshold limit for exposure control ---- Occupation exposure limits**

Material	ACGIH TLV		Remark
	TWA	STEL	
Toluene	20 ppm	-	
Acetone	500 ppm	750 ppm	
Isopropanol	200 ppm	400 ppm	
Butyl Glycol Ether	20 ppm	-	
Methyl Ethyl Ketone	200 ppm	300 ppm	

**SAFETY DATA SHEET**

Date of Issue: 30.08.2023

Version: 2.0

<b>Appropriate engineering control</b>	The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Use sealed systems as far as possible. Adequate ventilation to control airborne concentrations below the exposure guidelines/limits are recommended. Eye washes and showers for emergency use.
<b>Individual protection measures</b>	
Respiratory protection	If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for organic gases and vapours [boiling point >65 °C (149 °F)] meeting EN14387. Where respiratory protective equipment is required, use a full-face mask. Where air-filtering respirators are unsuitable (e.g., airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus.
Hand protection	Using gloves constructed of chemical resistant materials such as heavy nitrile rubber if frequent or prolonged contact is expected.  Neoprene or PVC gloves also be using in case of incidental contact or splash protection.  Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly.
Eye protection	Chemical splash goggles (chemical monogoggles). Eye washes and showers for emergency use are recommended to the work area.
Protective clothing	Protective gloves, safety shoes and boots are recommended.
Remarks	Personal protective equipment is not considered to long term solution of exposure control. Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

**SAFETY DATA SHEET**

Date of Issue: 30.08.2023

Version: 2.0

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Appearance</b>	Colourless liquid.
<b>Odor</b>	Characteristic odor.
<b>Initial Boiling Point</b>	No data
<b>Flammability limits in air</b>	No data
<b>Flash point</b>	8 - 10 °C (ASTM 6450)
<b>Viscosity (Kinematic)</b>	< 20 mm <sup>2</sup> /sec at 25° C
<b>Specific Gravity (water = 1)</b>	0.700 – 0.900 at 25 °C
<b>Water solubility</b>	Immiscible

**10. STABILITY AND RELIABILITY**

<b>Chemical stability</b>	Stable under normal conditions of use.
<b>Possibility of hazardous reaction</b>	No data.
<b>Condition to avoid</b>	Avoid from heat, sparks, open flames and other ignition sources.
<b>Incompatible materials</b>	Strong oxidizing agent.
<b>Hazardous decomposition products</b>	Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases, including carbon monoxide, carbon dioxide and other organic compounds may be evolved when this material undergoes combustion or thermal or oxidative degradation.

**11. TOXICOLOGICAL INFORMATION**

<b>Basis of assessment</b>	Information given is based on product data, mixtures of product and/ or the similar product and/ or ingredients.
<b>Acute oral toxicity</b>	Low toxicity: LD50 > 5,000 mg/kg
<b>Acute dermal toxicity</b>	Expected to be low of toxicity.
<b>Acute inhalation toxicity</b>	Expected to be low of toxicity.
<b>Skin corrosion/ irritation</b>	Causes skin irritation. Prolong or repeated exposure may cause skin dryness or dermatitis.
<b>Serious eye damage/ irritation</b>	Causes serious eye irritation.



**SAFETY DATA SHEET**

Date of Issue: 30.08.2023

Version: 2.0

<b>Respiratory tract irritation</b>	High concentration of vapor exposure may cause the irritation of respiratory tract.
<b>Respiratory or skin sensitization</b>	Not expected to be a sensitizer.
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways. Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.
<b>Germ cell mutagenicity</b>	Not mutagenic.
<b>Carcinogenicity</b>	Not expected to be a carcinogenic.
<b>Reproductive and Developmental Toxicity</b>	Suspected of damaging to fertility or the unborn child. Does not impair fertility.
<b>Specific Target Organ Toxicity (Single)</b>	Vapors may cause drowsiness and dizziness.
<b>Specific Target Organ Toxicity (Repeated)</b>	Central nervous system: repeated exposure affects the nervous system. Effects were seen at high doses only. Abuse of vapours has been associated with organ damage and death.

**12. ECOLOGICAL INFORMATION**

<b>Basis for Assessment</b>	The information given below is based partly on a knowledge of the components and the ecotoxicology of similar products.
<b>Acute Toxicity</b>	
Fish	Practically non-toxic: LC/ EC/ IC50 > 100 mg/ l
Aquatic invertebrates	Practically non-toxic: LC/ EC/ IC50 > 100 mg/ l
Algae	Practically non-toxic: LC/ EC/ IC50 > 100 mg/ l
Micro organism	Practically non-toxic: LC/ IC/ IC50 > 100 mg/ l
<b>Mobility</b>	Floats on water. Adsorbs to soil and has low mobility. May contaminate ground water.
<b>Persistence/degradability</b>	Readily biodegradable. Oxidized rapidly by photo-chemical reactions in air.
<b>Bioaccumulative potential</b>	Not expected to bio-accumulate significantly.

**SAFETY DATA SHEET**

Date of Issue: 30.08.2023

Version: 2.0

**13. DISPOSAL CONSIDERATION**
**Material disposal**

Recover or recycle if possible. It is responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses. Waste product should not be allowed to contaminate soil or water.

**Container disposal**

Drain container thoroughly. After draining, vent in a safe place away from sparks and fire. Residues may cause an explosion hazard. Do not puncture, cut or weld uncleaned drums. Send to drum recover or metal reclaimer.

**Local Legislation**

Disposal should be in accordance with applicable regional, national, and local laws and regulations. Send a disposal container to drum recover or metal reclaimer.

**14. TRANSPORT INFORMATION**

	ADR /RID	IMDG	IATA
UN Number	1263	UN 1263	1263
Proper Shipping Name	Paint and related material (Flammable)	PAINT AND RELATED MATERIAL (FLAMMABLE)	Paint and related material (Flammable)
Class	3	3	3
Packing group	II	II	II
Environmentally Hazardous	No	NO	-

**15. REGULATORY INFORMATION**

- Hazardous substances ACT, B.E. 2535 (1992)
- Notification of statement of the hazardous substances committee subject to Transportation of Dangerous Goods by road B.E. 2545 (2002)
- Notification of the Ministry of Industry subject to responsibility of Department of Industrial Works for hazardous substances

**SAFETY DATA SHEET**

Date of Issue: 30.08.2023

Version: 2.0

containment B.E. 2551 (2008)

- Notification of the Ministry of Industry subject to Globally Harmonized System of Classification and Labelling of Chemicals (GHS) B.E. 2555 (2012)

**16. OTHER INFORMATION**
**Remark 1 (Abbreviation)**

STOT - Specific Target Organs Toxicity

CAS No. – the Chemical Abstracts Service Number

ACGIH – American Conference of Governmental Industrial Hygienists

TLV – Threshold Limit Values

TWA – Time-Weighted Average

STEL – Short-Term Exposure Limit

LC50 – Lethal Concentration fifty

EC50 – half maximal Effective Concentration

IC50 – half maximal Inhibitory Concentration

NOEC – No Observed Effect Concentration

NOEL – No Observed Effect Level

ADR/ RID – The Agreements Concerning the international Carriage of Dangerous Goods by Rail (RID) and by Road (ADR)

IMDG – International Maritime Dangerous Goods

IATA – International Air Transport Association

**Disclaimer**

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be constructed as guaranteeing any specific property of the product.

All rights reserved to inform the precise quantity of constituents in the product.

By reason is confidential of the company which could not reveal or propagate to the public.