



URAI PAINTS
www.urpaints.com

ATM RED OXIDE PRIMER no. 1024

Bulletin no.

Description	A speicalized formulation of red oxide primer based on modified alkyd resin and red oxide pigments. It is designed to provide an excellent adhesion and quick dry coating. Good corrosion resistance and helps to enhance the adhesion between surface and top coating.																																										
Application	Suitable to be using as primer for steel or metal surfaces such as handrail, grills for windows, curved steel, machines, etc.																																										
Technical Data	<table><tr><td>Product type</td><td>:</td><td colspan="2">Alkyd resin</td></tr><tr><td>Appearance</td><td>:</td><td colspan="2">Viscous liquid in dark brown colour.</td></tr><tr><td>Film type</td><td>:</td><td colspan="2">Egg shell matt</td></tr><tr><td>Specific Gravity (water = 1)</td><td>:</td><td colspan="2">1.4 – 1.5</td></tr><tr><td>Viscosity</td><td>:</td><td colspan="2">100 - 105 KU at 25 °C</td></tr><tr><td>Application tools</td><td>:</td><td colspan="2">Brush, roller or spray</td></tr><tr><td>Diluent</td><td>:</td><td colspan="2">Lion brand turpentine substitute</td></tr><tr><td>Drying time at 25 °C</td><td></td><td colspan="2"></td></tr><tr><td>- Dry to touch</td><td>:</td><td colspan="2">15 - 30 minutes.</td></tr><tr><td>- Dry to recoat</td><td>:</td><td colspan="2">4 - 6 hours.</td></tr></table>			Product type	:	Alkyd resin		Appearance	:	Viscous liquid in dark brown colour.		Film type	:	Egg shell matt		Specific Gravity (water = 1)	:	1.4 – 1.5		Viscosity	:	100 - 105 KU at 25 °C		Application tools	:	Brush, roller or spray		Diluent	:	Lion brand turpentine substitute		Drying time at 25 °C				- Dry to touch	:	15 - 30 minutes.		- Dry to recoat	:	4 - 6 hours.	
Product type	:	Alkyd resin																																									
Appearance	:	Viscous liquid in dark brown colour.																																									
Film type	:	Egg shell matt																																									
Specific Gravity (water = 1)	:	1.4 – 1.5																																									
Viscosity	:	100 - 105 KU at 25 °C																																									
Application tools	:	Brush, roller or spray																																									
Diluent	:	Lion brand turpentine substitute																																									
Drying time at 25 °C																																											
- Dry to touch	:	15 - 30 minutes.																																									
- Dry to recoat	:	4 - 6 hours.																																									
Painting System	<table><tr><td>Surface preparation :</td><td colspan="3"></td></tr><tr><td colspan="4">Make sure the surface to be painted is free from dust, dirt, grease, waxy contaminant and loose particles. Rust or millscales should be removed.</td></tr><tr><td>Primer coating :</td><td colspan="3"></td></tr><tr><td>- ATM Red Oxide Primer no. 1024</td><td></td><td>1 – 2 coats</td><td></td></tr><tr><td>- ATM Gloss Enamel</td><td></td><td>2 – 3 coats</td><td></td></tr></table>			Surface preparation :				Make sure the surface to be painted is free from dust, dirt, grease, waxy contaminant and loose particles. Rust or millscales should be removed.				Primer coating :				- ATM Red Oxide Primer no. 1024		1 – 2 coats		- ATM Gloss Enamel		2 – 3 coats																					
Surface preparation :																																											
Make sure the surface to be painted is free from dust, dirt, grease, waxy contaminant and loose particles. Rust or millscales should be removed.																																											
Primer coating :																																											
- ATM Red Oxide Primer no. 1024		1 – 2 coats																																									
- ATM Gloss Enamel		2 – 3 coats																																									
Coverage	8 - 12 sq.m/ litre /coat																																										
Storage & Shelf life	Maximum 5 years in sealed container. Keep away from heat/ sparks/ open flames. No smoking. Keep container in a cool dry and well-ventilated place. Protect from direct sunlight. When not in use, keep container tightly closed and use again after correct storage.																																										
Safety, Health and Environment Information	Keep out of reach of children. Use only outdoors or in a well-ventilated area. Wear protective gloves, eye and face protection. Avoid contact with skin or eyes. Wash thoroughly after handling. IF ON SKIN; Wash with plenty of soap and rinse skin with clean water. IF IN EYES, Rinse cautiously with water for several minutes. Do not empty into drains. Avoid release to the environment.																																										
Packing	0.875 Litres, 3.5 Litres and 17.5 Litres.																																										

DISCLAIMER: The above information provided herein is based on the present state of our knowledge and practical experience. Since the product is often used under different conditions beyond our control. We cannot guarantee anything but the quality of the product itself. All the rights are reserved to change the data without any notice.