URAI PAINTS
www.urpaints.com

Technical Data Sheet

# LOBSTER Red Oxide Primer no. 1024

Bulletin no. .....

## Description

A speicialized formulation of red oxide primer based on modified alkyd resin and red oxide pigments. It is designed to provide an excellent adhesion and quick dry coating. Good corrosion resistance and helps to enhance the adhesion between surface and top coating.

## Application

Suitable to be using as primer for steel or metal surfaces such as handrail, grills for windows, curved steel, machines, etc.

## Technical Data

| | | |
|---|---|---|
| Product type | : | Alkyd resin |
| Appearance | : | Viscous liquid in dark brown colour. |
| Film type | : | Egg shell matt |
| Specific Gravity (water = 1) | : | 1.4 – 1.5 |
| Viscosity | : | 100 - 105 KU at 25 °C |
| Application tools | : | Brush, roller or spray |
| Diluent | : | Lion brand turpentine substitute |
| Drying time at 25 °C | | |
| - Dry to touch | : | 15 - 30 minutes. |
| - Dry to recoat | : | 4 - 6 hours. |

## Painting System

Surface preparation :

Make sure the surface to be painted is free from dust, dirt, grease, waxy contaminant and loose particles. Rust or millscales should be removed.

Primer coating :

- Lobster Red Oxide Primer no. 1024 — 1 – 2 coats
- Lobster Alkyd Enamel — 2 – 3 coats

## Coverage

8 - 12 sq.m/ litre /coat

## Storage & Shelf life

Maximum 5 years in sealed container. Keep away from heat/ sparks/ open flames. No smoking. Keep container in a cool dry and well-ventilated place. Protect from direct sunlight. When not in use, keep container tightly closed and use again after correct storage.

## Safety, Health and Environment Information

Keep out of reach of children. Use only outdoors or in a well-ventilated area. Wear protective gloves, eye and face protection. Avoid contact with skin or eyes. Wash thoroughly after handling. IF ON SKIN; Wash with plenty of soap and rinse skin with clean water. IF IN EYES, Rinse cautiously with water for several minutes. Do not empty into drains. Avoid release to the environment.

## Packing

0.280 Litres, 0.875 Litres, 3.5 Litres and 17.5 Litres.

***DISCLAIMER:*** *The above information provided herein is based on the present state of our knowledge and practical experience. Since the product is often used under different conditions beyond our control. We cannot guarantee anything but the quality of the product itself. All the rights are reserved to change the data without any notice.*

Sales office: 52, 54 Soi Sathorn 11 (Sect. 3) South Sathorn rd., Yannawaa, Sathorn, Bangkok 10120. Tel: +66 2 312 1049-50, +66 2 750 4808-9 Fax: +66 2 312 1163