



URAI PAINTS
www.urpaints.com

Beauty Acrylic Alkali Resisting Primer no. EX-300

Bulletin no.

Description	An ultimate formula which developed from special acrylic resin to provide an exceptional property for alkali resistance on new surfaces. Easy to apply. Enhance the adhesion between substrates and top coating. Suitable for both of exterior and interior application.		
Application	It is recommended for new surfaces priming to apply on both of exterior and interior. Excellent resistance against to alkali and fungus.		
Technical Data	Product type	:	Acrylic Co-polymer
	Appearance	:	Off white colour, viscous liquid.
	Film type	:	Egg shell matt
	Specific Gravity (water = 1)	:	1.4 – 1.5
	Viscosity	:	105 – 110 KU at 25 °C
	Application tools	:	Brush – Roller – Conventional spray
	Drying time at 25 °C		
	- Dry to touch	:	15 - 30 minutes.
	- Dry to recoat	:	1 – 2 hours.
Painting System	Leaves new surfaces to be fully cured at least 1 month to avoid any damaging from efflorescence. Clean the surface to be free from dust, dirt, grease or any loose particles.		
	- Priming by Beauty Acrylic Alkali Resisting Primer 1 coat.		
	For Interior	Top coating by Beauty Acrylic Emulsion Paint for INT	2-3 coats
	For Exterior	Top coating by Beauty Acrylic Emulsion Paint for EXT	2-3 coats
Coverage	35 – 40 sq.m/ gallon. /coat		
Storage & Shelf life	Maximum 2 years in sealed container. Keep container in a cool dry and well-ventilated place. Protect from direct sunlight. When not in use, keep container tightly closed and use again after correct storage.		
Safety, Health and Environment Information	Keep out of reach of children. Use in a well-ventilated area. Avoid contact with skin or eyes. Wash thoroughly after handling. If on skin, wash with plenty of soap and rinse skin with clean water. If in eyes, rinse cautiously with water for several minutes. Do not use empty container for food stuff. Do not empty into drains.		
Packing	3.6 Litres, 10 Litres and 18 Litres.		

DISCLAIMER: The above information provided herein is based on the present state of our knowledge and practical experience. Since the product is often used under different conditions beyond our control. We cannot guarantee anything but the quality of the product itself. All the rights are reserved to change the data without any notice.