



URAI PAINTS
www.urpaints.com

Lobster Pure Clear Acrylic Finish Solvent Base: A100

Bulletin no.

Description	An acrylic solvent base to provide extra gloss and clear finish. Excellent adhesion. High durability coating and very good protection against extreme weather changes. It helps to protect surface from dirt, fungus and algae. Great for waterproofing top coat.																				
Application	Suitable to apply as clear top coat on many kinds of substrates e.g. masonry, plaster, sand wash, trench mortar, clay tile, wood or cement, etc.																				
Technical Data	<table><tr><td>Product type</td><td>: Acrylic resin</td></tr><tr><td>Appearance</td><td>: Clear liquid with characteristic odour.</td></tr><tr><td>Finish</td><td>: Very high Gloss</td></tr><tr><td>Specific Gravity (water = 1)</td><td>: 0.8 – 0.9</td></tr><tr><td>Viscosity (Ford cup no. 4)</td><td>: 20 – 25 sec at 25 °C</td></tr><tr><td>Application tools</td><td>: Brush, roller or spray</td></tr><tr><td>Diluent</td><td>: Lobster Enamel Thinner no. T07 or Lion brand turpentine substitute no. T21</td></tr><tr><td colspan="2">Drying time at 25 °C</td></tr><tr><td>- Dry to touch</td><td>: Less than 1 hour</td></tr><tr><td>- Dry to recoat</td><td>: 2 - 4 hours.</td></tr></table>	Product type	: Acrylic resin	Appearance	: Clear liquid with characteristic odour.	Finish	: Very high Gloss	Specific Gravity (water = 1)	: 0.8 – 0.9	Viscosity (Ford cup no. 4)	: 20 – 25 sec at 25 °C	Application tools	: Brush, roller or spray	Diluent	: Lobster Enamel Thinner no. T07 or Lion brand turpentine substitute no. T21	Drying time at 25 °C		- Dry to touch	: Less than 1 hour	- Dry to recoat	: 2 - 4 hours.
Product type	: Acrylic resin																				
Appearance	: Clear liquid with characteristic odour.																				
Finish	: Very high Gloss																				
Specific Gravity (water = 1)	: 0.8 – 0.9																				
Viscosity (Ford cup no. 4)	: 20 – 25 sec at 25 °C																				
Application tools	: Brush, roller or spray																				
Diluent	: Lobster Enamel Thinner no. T07 or Lion brand turpentine substitute no. T21																				
Drying time at 25 °C																					
- Dry to touch	: Less than 1 hour																				
- Dry to recoat	: 2 - 4 hours.																				
Painting System	Surface preparation : Make sure the surface to be painted is free from dust, dirt, grease, waxy contaminant and loose particles. Rust or millscale should be removed. Coating System : This product is ready to use, no need for a dilution. Apply by brush, roller or spray gun on prepared substrate 1-2 coats by keep an interval to recoat 2-4 hours. If dilution is needed or clean up tools after application. Using Lobster Alkyd Enamel no. T07 or Lion Brand Turpentine Substitute no. T21 by recommendation.																				
Coverage	40 - 45 sq.m/ gallon /coat																				
Storage & Shelf life	Maximum 5 years in sealed container. Keep away from heat/ sparks/ open flames. No smoking. Keep container in a cool dry and well-ventilated place. Protect from direct sunlight. When not in use, keep container tightly closed and use again after correct storage.																				
Safety, Health and Environment Information	Keep out of reach of children. Use only outdoors or in a well-ventilated area. Wear protective gloves, eye and face protection. Do not breathe vapours/ mist/ spray/ fume. Use only outdoors																				

DISCLAIMER: The above information provided herein is based on the present state of our knowledge and practical experience. Since the product is often used under different conditions beyond our control. We cannot guarantee anything but the quality of the product itself. All the rights are reserved to change the data without any notice.



URAI PAINTS
www.urpaints.com

Lobster Pure Clear Acrylic Finish Solvent Base: A100

Bulletin no.

or in a well-ventilated area. Avoid contact with skin or eyes. Wash thoroughly after handling.
IF ON SKIN; Wash with plenty of soap and rinse skin with clean water. IF IN EYES, Rinse cautiously with water for several minutes. Do not empty into drains. Avoid release to the environment.

Packing

0.48 Litres/ 0.85 Litres / 3.4 Litres

DISCLAIMER: The above information provided herein is based on the present state of our knowledge and practical experience. Since the product is often used under different conditions beyond our control. We cannot guarantee anything but the quality of the product itself. All the rights are reserved to change the data without any notice.