



U-90 Acrylic Emulsion Paint for Interior

Bulletin no.

Description	U-90 Acrylic Emulsion Paint for Interior is formulated from Acrylic Polymer. That is a choice for economy paint. It provides smooth and beautiful finish. Good protection against fungus.																														
Application	It is an ideal for interior walls decoration e.g. concrete, masonry, brick, etc.																														
Technical Data	<table border="1"><tr><td>Product type</td><td>:</td><td>Acrylic Co-polymer</td></tr><tr><td>Appearance</td><td>:</td><td>Viscous liquid in white color.</td></tr><tr><td>Film type</td><td>:</td><td>Matt</td></tr><tr><td>pH</td><td>:</td><td>8-10</td></tr><tr><td>Density</td><td>:</td><td>1.40 – 1.70</td></tr><tr><td>Solid content</td><td>:</td><td>Not available</td></tr><tr><td>Viscosity</td><td>:</td><td>105 – 110 KU at 25 °C</td></tr><tr><td>Application</td><td>:</td><td>Brush, Roller or Spray gun</td></tr><tr><td>Dilution</td><td>:</td><td>Water 10 %</td></tr><tr><td>Drying time</td><td>:</td><td>- Dry to touch 30-60 minutes - Dry to recoat 2-3 hours</td></tr></table>	Product type	:	Acrylic Co-polymer	Appearance	:	Viscous liquid in white color.	Film type	:	Matt	pH	:	8-10	Density	:	1.40 – 1.70	Solid content	:	Not available	Viscosity	:	105 – 110 KU at 25 °C	Application	:	Brush, Roller or Spray gun	Dilution	:	Water 10 %	Drying time	:	- Dry to touch 30-60 minutes - Dry to recoat 2-3 hours
Product type	:	Acrylic Co-polymer																													
Appearance	:	Viscous liquid in white color.																													
Film type	:	Matt																													
pH	:	8-10																													
Density	:	1.40 – 1.70																													
Solid content	:	Not available																													
Viscosity	:	105 – 110 KU at 25 °C																													
Application	:	Brush, Roller or Spray gun																													
Dilution	:	Water 10 %																													
Drying time	:	- Dry to touch 30-60 minutes - Dry to recoat 2-3 hours																													
Application Instruction	<ul style="list-style-type: none">● Surface Preparation New surface: Leave the surface at least 1 month to completely cured and dried. Substrate must be free from dust, dirt, grease or loose particles. Old surface: the surface should be clean and dry. If fungus or mildew growth must be cleaned off before coating.● Primer New surface: Priming by Acrylic Alkali Resisting Primer Ex-300 1 coat Old surface: Priming by Contact Primer V-1100 1 coat● Coating System Apply U-90 Acrylic Emulsion Paint for Interior to top coat 2-3 coats. Drying time to recoat is 2-3 hours by approximately.																														
Coverage	35 – 40 sq.m / gallon /coat																														
Storage & Shelf life	Maximum 5 years in sealed container. Protect from sunlight. Keep container tightly closed when not in use and use again after correct storage. Keep it in well-ventilated place.																														



URAI PAINTS
www.urapaints.com

U-90 Acrylic Emulsion Paint for Interior

Bulletin no.

Safety, Health and Environment Information

- Keep out of reach of children.
- Use in a well-ventilated area.
- Avoid contact with skin or eyes.
- If on skin, wash with plenty of soap and rinse skin with clean water.
- If in eyes, rinse cautiously with water for several minutes.
- Do not use empty container for food stuff.
- Avoid release to the environment.

Packing

18 Liters (White)

DISCLAIMER: *The above information provided herein is based on the present state of our knowledge and practical experience. Since the product is often used under different conditions beyond our control. We cannot guarantee anything but the quality of the product itself. All the rights are reserved to change the data without any notice.*

Sales office: 52, 54 Soi Sathorn 11 (Sect. 3)
South Sathorn rd., Yannawaa, Sathorn,
Bangkok 10120.
Tel: +66 2 312 1049-50, +66 2 750 4808-9
Fax: +66 2 312 1163
www.urpaints.com