



URAI PAINTS
www.urapaints.com

ATM Synthetic Resin Aluminium Paint No. U-000

Bulletin no.

Description	ATM Synthetic Resin Aluminium Paint is specially formulated with high quality of Aluminium paste. Long lasting colour retention and durability. Good adhesion to the substrate. Excellent in weather resistance.		
Application	It is an ideal for using to decorate on variety of substrate; wood, metal or steel.		
Technical Data	Product type	:	Synthetic Resin Aluminium Paint
	Appearance	:	Viscous liquid in Aluminium colour
	Density	:	0.900 – 1.000
	Solid content	:	Not available
	Viscosity (Ford cup # 4)	:	14-18 Sec at 25 °C
	Application	:	Brush, Spray
	Dilution	:	Ready to use
	Drying time	:	- Dry to touch 1-2 hours - Dry to recoat 3-4 hours
Application Instruction	- Surface Preparation - Metal Surface - Old metal surface: Flake surface must be eliminated. Then, remove the rust or mill scales. - New metal surface: the surface should be clean and dry. If there are oil, grease or waxy contaminate must be cleaned off before coating. - Wood Surface - Old wood surface: Flake surface must be eliminated. Remove splinter with sandpaper to enhance better adhesion. - New wood surface: smooth wood surface with sandpaper and cleaning the substrate to free from oil, grease and waxy contaminate. - Primer - Metal surface: Priming by ATM Grey Primer No. 1040. 1 coat - Wood surface: Priming by ATM Undercoat White No. 1600. 1 coat - Coating System Apply ATM Synthetic Resin Aluminium Paint to top coat 2 coats by brush or Spray. Drying time to recoat is 3-4 hours by approximately.		
Coverage	30 – 40 sq.m / gallon /coat		

DISCLAIMER: The above information provided herein is based on the present state of our knowledge and practical experience. Since the product is often used under different conditions beyond our control. We cannot guarantee anything but the quality of the product itself. All the rights are reserved to change the data without any notice.

Sales office: 52, 54 Soi Sathorn 11 (Sect. 3)
South Sathorn rd., Yannawaa, Sathorn,
Bangkok 10120.
Tel: +66 2 312 1049-50, +66 2 750 4808-9
Fax: +66 2 312 1163
www.urapaints.com



URAI PAINTS
www.urapaints.com

ATM Synthetic Resin Aluminium Paint No. U-000

Bulletin no.

Storage & Shelf life	Maximum 5 years in sealed container. Protect from sunlight. Keep container tightly closed when not in use and use again after correct storage. Keep it in well-ventilated place.
Safety, Health and Environment Information	● Keep out of reach of children. ● Keep away from heat/ sparks/ open flames. No smoking ● Use in a well-ventilated area. ● Avoid contact with skin or eyes. ● If on skin, wash with plenty of soap and rinse skin with clean water. ● If in eyes, rinse cautiously with water for several minutes. ● Avoid release to the environment.
Packing	0.875 Litres / 3.5 Litres / 17.5 Litres

DISCLAIMER: The above information provided herein is based on the present state of our knowledge and practical experience. Since the product is often used under different conditions beyond our control. We cannot guarantee anything but the quality of the product itself. All the rights are reserved to change the data without any notice.

Sales office: 52, 54 Soi Sathorn 11 (Sect. 3)
South Sathorn rd., Yannawaa, Sathorn,
Bangkok 10120.
Tel: +66 2 312 1049-50, +66 2 750 4808-9
Fax: +66 2 312 1163
www.urpaints.com