



U-90 Vinyl Anti-Fouling Paint No.60

Bulletin no.

Description	U-90 Vinyl anti-fouling paint is a specially designed coating based on vinyl resins with easy use, quick dry, excellent adhesion and high solid coating. It consists of cuprous oxide that helps to prevent the growth of organisms on vessel's hull. Keep long lasting performance and durability. Free from heavy metal. Environmental friendly.																											
Application	An idealized coating with high efficacy to prevent the growth of organism on the hull of ship or boat. The product is ready to use, surface haven't to priming.																											
Technical Data	<table border="1"><tr><td>Product type</td><td>:</td><td>Vinyl resin anti-fouling paint.</td></tr><tr><td>Appearance</td><td>:</td><td>Viscous liquid red-brown colour.</td></tr><tr><td>Texture</td><td>:</td><td>matt</td></tr><tr><td>Specific Gravity (water = 1)</td><td>:</td><td>1.700-1.800</td></tr><tr><td>Solid content</td><td>:</td><td>60-80 %</td></tr><tr><td>Viscosity</td><td>:</td><td>83-86 KU at 25 °C</td></tr><tr><td>Application</td><td>:</td><td>Brush, Roller or Spray Gun</td></tr><tr><td>Dilution</td><td>:</td><td>Ready to use.</td></tr><tr><td>Drying time</td><td>:</td><td>- Dry to touch 30 minutes - Dry to recoat 2 hrs.</td></tr></table>	Product type	:	Vinyl resin anti-fouling paint.	Appearance	:	Viscous liquid red-brown colour.	Texture	:	matt	Specific Gravity (water = 1)	:	1.700-1.800	Solid content	:	60-80 %	Viscosity	:	83-86 KU at 25 °C	Application	:	Brush, Roller or Spray Gun	Dilution	:	Ready to use.	Drying time	:	- Dry to touch 30 minutes - Dry to recoat 2 hrs.
Product type	:	Vinyl resin anti-fouling paint.																										
Appearance	:	Viscous liquid red-brown colour.																										
Texture	:	matt																										
Specific Gravity (water = 1)	:	1.700-1.800																										
Solid content	:	60-80 %																										
Viscosity	:	83-86 KU at 25 °C																										
Application	:	Brush, Roller or Spray Gun																										
Dilution	:	Ready to use.																										
Drying time	:	- Dry to touch 30 minutes - Dry to recoat 2 hrs.																										
Application Instruction	<p>Instruction</p> <ol style="list-style-type: none">1. Clean the surface and leaves it dry. Using primer to apply on metal surface before go to next step.2. Stir paint thoroughly before apply. No need for a dilution3. Apply by brush, roller or spray. Recommend to apply for 2 coats; drying time to recoat is 6 hrs.																											
Coverage	30 – 35 sq.m / gallon /coat																											
Storage & Shelf life	Maximum 5 years in sealed container. Protect from sunlight. Keep container tightly closed when not in use and use again after correct storage. Keep it in well-ventilated place.																											



URAI PAINTS
www.uraipaints.com

U-90 Vinyl Anti-Fouling Paint No.60

Bulletin no.

Safety, Health and Environment Information

- Keep out of reach of children.
- Keep away from heat/ sparks/ open flames. No smoking
- Use in a well-ventilated area.
- Avoid contact with skin or eyes.
- If on skin, wash with plenty of soap and rinse skin with clean water.
- If in eyes, rinse cautiously with water for several minutes.
- Avoid release to the environment.

Packing

0.946 Litres / 1.892 Litres / 3.785 Litres

DISCLAIMER: *The above information provided herein is based on the present state of our knowledge and practical experience. Since the product is often used under different conditions beyond our control. We cannot guarantee anything but the quality of the product itself. All the rights are reserved to change the data without any notice.*

Sales office: 52, 54 Soi Sathorn 11 (Sect. 3)
South Sathorn rd., Yannawa, Sathorn,
Bangkok 10120.
Tel: +66 2 312 1049-50, +66 2 750 4808-9
Fax: +66 2 312 1163
www.uraipaints.com