URAI PAINTS
www.uraipaints.com

Technical Data Sheet

ATM Motorcycle Spray

Bulletin no. .....

Description

ATM motorcycle spray is formulated from special acrylic resin with nitrocellulose. That gives the colourful candy tone finish. The properties of this product are quick dry, high gloss finish and excellent adhesion.

Application

It is idealized for make up or decorate artwork or parts of motorbike.

Technical Data

Product type	:	Nitrocellulose and Acrylic Lacquer Resin
Appearance	:	Liquid spray regarding to catalog.
Film type	:	Gloss/Matt
Viscosity (Ford cup # 4)	:	12-14 sec at 25 °C (In liquid state)
Flash point	:	-73 °C (Based on the lowest flash point material, spray propellent (LPG – Liquefied Petroleum Gas))
Air vapour pressure	:	4.5 – 5 kg/cm^2 at 30 °C
Drying time	:	- Dry to touch 15 minutes - Dry to recoat 1 hours

Application Instruction

Surface Preparation

The surface should be clean and dry. If there are oil or waxy contaminate must be cleaned off before priming.

Priming

Priming by ATM spray candy tone No. A100 2 coat. Drying time to recoat 10 minutes by approximately.

Coating

- Shake ATM motorcycle spray can thoroughly 2 minutes before using and shake periodically during spray.
- Spray from a distance of about 1 foot.
- For better result apply several thin coatings with an interval of 10 minutes.
- After spraying turn can upside down and press spray head to clean the spray nozzle.

Recommendation

Recommend to apply ATM spray clear coating No. A-10 as last step to get a shiny and sparkling film.

Coverage

1.2-1.5 sq.m / coat / can (270 g)

DISCLAIMER: *The above information provided herein is based on the present state of our knowledge and practical experience. Since the product is often used under different conditions beyond our control. We cannot guarantee anything but the quality of the product itself.*
All the rights are reserved to change the data without any notice.

Sales office: 52, 54 Soi Sathorn 11 (Sect. 3)
South Sathorn rd., Yannawa, Sathorn,
Bangkok 10120.
Tel: +66 2 312 1049-50, +66 2 750 4808-9
Fax: +66 2 312 1163
www.uraipaints.com

ATM Motorcycle Spray

Bulletin no. .....

Storage & Shelf life	Maximum 3 years in sealed container. Protect from sunlight. Do not expose to temperatures exceeding 25-30 °C. Keep it in well-ventilated place.
Safety, Health and Environment Information	• Keep out of reach of children. • Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. • Use in a well-ventilated area. • Do not spray on an open flame or other ignition source. • If on skin, wash with plenty of soap and rinse skin with clean water. • If in eyes, rinse cautiously with water for several minutes. • Do not pierce or burn, even after use. • Avoid release to the environment.
Packing	270 g

DISCLAIMER: *The above information provided herein is based on the present state of our knowledge and practical experience. Since the product is often used under different conditions beyond our control. We cannot guarantee anything but the quality of the product itself.*
All the rights are reserved to change the data without any notice.

Sales office: 52, 54 Soi Sathorn 11 (Sect. 3)
South Sathorn rd., Yannawa, Sathorn,
Bangkok 10120.
Tel: +66 2 312 1049-50, +66 2 750 4808-9
Fax: +66 2 312 1163
www.uraipaints.com