



# ATM Spray Acrylic Lacquer Gold Paint No. G6000

Bulletin no. ....

<b>Description</b>	ATM spray acrylic lacquer gold paint is a specially formulated from high quality of acrylic resin and gold pigment. That gives look gold finish. It is not real gold, just looks like gold. Another excellent property is quick drying with good adhesion.																					
<b>Application</b>	It is ideal to make a basic item to be elegant in seconds. More luxury in appearance. Great for decoration to crafts, furniture or artworks.																					
<b>Technical Data</b>	<table border="1"><tr><td>Product type</td><td>:</td><td>Acrylic Resin</td></tr><tr><td>Appearance</td><td>:</td><td>Colour liquid spray regarding to catalog.</td></tr><tr><td>Film type</td><td>:</td><td>Gloss</td></tr><tr><td>Viscosity (Ford cup # 4)</td><td>:</td><td>12-14 sec at 25 °C (In liquid state)</td></tr><tr><td>Flash point</td><td>:</td><td>-73 °C (Based on the lowest flash point material, spray propellant (LPG – Liquefied Petroleum Gas))</td></tr><tr><td>Air vapour pressure</td><td>:</td><td>4.5 – 5 kg/cm<sup>2</sup> at 30 °C</td></tr><tr><td>Drying time</td><td>:</td><td>- Dry to touch    15 minutes - Dry to recoat    1 hour</td></tr></table>	Product type	:	Acrylic Resin	Appearance	:	Colour liquid spray regarding to catalog.	Film type	:	Gloss	Viscosity (Ford cup # 4)	:	12-14 sec at 25 °C (In liquid state)	Flash point	:	-73 °C (Based on the lowest flash point material, spray propellant (LPG – Liquefied Petroleum Gas))	Air vapour pressure	:	4.5 – 5 kg/cm <sup>2</sup> at 30 °C	Drying time	:	- Dry to touch    15 minutes - Dry to recoat    1 hour
Product type	:	Acrylic Resin																				
Appearance	:	Colour liquid spray regarding to catalog.																				
Film type	:	Gloss																				
Viscosity (Ford cup # 4)	:	12-14 sec at 25 °C (In liquid state)																				
Flash point	:	-73 °C (Based on the lowest flash point material, spray propellant (LPG – Liquefied Petroleum Gas))																				
Air vapour pressure	:	4.5 – 5 kg/cm <sup>2</sup> at 30 °C																				
Drying time	:	- Dry to touch    15 minutes - Dry to recoat    1 hour																				
<b>Application Instruction</b>	<p><b>Surface Preparation</b></p> <p>The surface should be clean and dry. If there are oil or waxy contaminate must be cleaned off before priming.</p> <p><b>Priming</b></p> <p>Priming by ATM spray acrylic primer yellow No. A118 for 2 coats. Drying time to recoat 15 minutes by approximately.</p> <p><b>Coating</b></p> <ul style="list-style-type: none"><li>● Shake ATM acrylic lacquer gold paint can thoroughly 2 minutes before using and shake periodically during spray.</li><li>● Spray from a distance of about 1 foot.</li><li>● For better result apply several thin coatings with an interval of 15 minutes.</li><li>● After spraying turn can upside down and press spray head to clean the spray nozzle.</li></ul> <p><b>Recommendation</b></p> <p>Recommend to apply ATM spray acrylic clear top coat No. A031 as last step to get a shiny and sparkling film</p>																					
<b>Coverage</b>	1.2-1.5 sq.m / coat / can (270 g)																					



URAI PAINTS  
[www.urapaints.com](http://www.urapaints.com)

# ATM Spray Acrylic Lacquer Gold Paint No. G6000

Bulletin no. ....

<b>Storage &amp; Shelf life</b>	Maximum 3 years in sealed container. Protect from sunlight. Do not expose to temperatures exceeding 25-30 °C. Keep it in well-ventilated place.
<b>Safety, Health and Environment Information</b>	<ul style="list-style-type: none"><li>● Keep out of reach of children.</li><li>● Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</li><li>● Use in a well-ventilated area.</li><li>● Do not spray on an open flame or other ignition source.</li><li>● If on skin, wash with plenty of soap and rinse skin with clean water.</li><li>● If in eyes, rinse cautiously with water for several minutes.</li><li>● Do not pierce or burn, even after use.</li><li>● Avoid release to the environment.</li></ul>
<b>Packing</b>	270 g

**DISCLAIMER:** The above information provided herein is based on the present state of our knowledge and practical experience. Since the product is often used under different conditions beyond our control. We cannot guarantee anything but the quality of the product itself. All the rights are reserved to change the data without any notice.

Sales office: 52, 54 Soi Sathorn 11 (Sect. 3)  
South Sathorn rd., Yannawa, Sathorn,  
Bangkok 10120.  
Tel: +66 2 312 1049-50, +66 2 750 4808-9  
Fax: +66 2 312 1163  
[www.urapaints.com](http://www.urapaints.com)