

TV Spray Acrylic Lacquer (Various colours for multi-purpose)

Bulletin no.

Description	TV spray acrylic lacquer is specially formulated from high quality of acrylic resin and nitrocellulose. It provides an exceptional property; Quick drying. Easy to paint with aerosol to give a colourful and gloss finish. Excellent adhesion to every substrate.	
Application	A universal coating that can be applied to many kinds of substrates such as steel, plastic, wood, etc.	
Technical Data	Product type	: Nitrocellulose and Acrylic Lacquer Resin
	Appearance	: Liquid spray regarding to catalog.
	Film type	: Gloss / Matt
	Viscosity	: 12-14 sec at 25 °C (In liquid state)
	Flash point	: -73 °C (Based on the lowest flash point material, spray propellent (LPG – Liquefied Petroleum Gas))
	Air vapour pressure	: 4.5 – 5 kg/cm² at 30 °C
	Drying time	: - Dry to touch 15 minutes - Dry to recoat 1 hours
Application Instruction	 Clean surface thoroughly to be free from rust, dirt and grease. Shake can thoroughly 2 minutes before using and shake periodically during spray. Spray from a distance of about 1 foot. For better result apply several thin coatings with an interval of 10 minutes. After spraying turn can upside down and press spray head to clean the spray nozzle. 	
Coverage	1.2 -1.5 sq.m / coat / can (270 g)	
Storage & Shelf life		container. Protect from sunlight. Do not expose to -30 °C. Keep it in well-ventilated place.

Fax: +66 2 312 1163 www.uraipaints.com



TV Spray Acrylic Lacquer (Various colours for multi-purpose)

Bulletin no.

Safety, Health and Environment Information	 Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use in a well-ventilated area. Do not spray on an open flame or other ignition source. If on skin, wash with plenty of soap and rinse skin with clean water. If in eyes, rinse cautiously with water for several minutes.
	Do not pierce or burn, even after use.Avoid release to the environment.
Packing	270 g

Fax: +66 2 312 1163

www.uraipaints.com