

# ATM Anti-Termite SD

Version 1.1

Date of issue 22/03/2021

Description	ATM Anti-termite SD, a milky white mixture which formulated to use for termite control
Description	in new buildings under construction and treatment for existing infested termite
	buildings.
	buildings.
Thailand Food and Drugs Administration	อย. วอส. 1377/2554
Registration No.	
Benefit	Anti-termite soil treatment is the ideal method for termite control by design to create
	an effective chemical barrier to prevent termite infestation for a long time.
Technical Data	Product type : Petroleum Naphtha mixture.
reciffical Data	
	Appearance : Viscous liquid in milky-white colour / Light odour
	Active ingredients : Cypermethrin 4% w/w
	Viscosity : 70 – 75 KU at 25 °C
	Specific gravity (water = 1) : 0.900 – 1.000 at 25 °C
	Application : Pouring, Shower, Low pressure spray.
Application Instruction	
	MIXING INSTRUCTION
	- Shake well before use.
	- Mix ATM Anti-Termite 250 ml. with water by the final finished dilution volume is
	10 Litres.
	- Stir the solution before taking to apply.
	- The finished dilution can be applied by a coarse spray nozzle (shower) and/or
	low-pressure spray (less than 25 PSI)
	- Partly use is not recommended, should be used up after mix well.
	RECOMENDATION BEFORE USING
	The product should only be applied by licensed technicians. All pesticide
	handlers must wear Personal Protective Equipment, PPE (long sleeves shirt, protective
	gloves, eye and face protection and safety shoes) to prevent any contaminates from
	the product mixtures. Obtain special instructions before use and do not handle until

all safety precautions have been read and understood.

Bangkok 10120. Tel: +66 2 312 1049-50, +66 2 750 4808-9 Fax: +66 2 312 1163 www.urpaints.com



# ATM Anti-Termite SD

Version 1.1

Date of issue 22/03/2021

### Application Instruction (continued)

#### **DIRECTION FOR USES**

#### 1. New buildings (Pre-Construction)

1.1 For the interior of building or foundation, after completion of the grading, apply the finished dilution of ATM Anti-Termite SD by coverage at 5-7 litres per sq.m. with shower or spray (low pressure). Make this treatment along the inside of foundation walls at the rate of finished dilution 6 litres/ metre. Cover the treated soil with a waterproof barrier such as polyethylene sheet. Complete by concrete slab pour which should be done in the same day as treatment.

1.2 For the exterior of building or foundation, trenching along the outside perimeter of wall by making 30 cm width  $\times$  15 – 30 cm depth which should not be over a depth of foundation. Apply the finished dilution of ATM Anti-Termite SD at the rate of 6 litres/ metre along the outside of wall. Filling the soil back into the trench and apply more the finished dilution with a ratio at 6 litres/ metre. Cover the treated zone by a plastic sheet. The application of this treatment should be finished within a same day.

#### 2. Existing buildings (Post-Construction)

- 2.1 Drill the holes on a building surface and/or concrete slab by keep a distance between holes about 30 cm.
- 2.2 Apply the finished dilution of ATM Anti-Termite SD by using low pressure spray to both of inside and outside of building. The rate of application is 2 litres per hole. The chemical can be applied to the outside perimeter of foundation by trenching along the concrete slab, 30 cm width X 30 cm depth. Keep a distance between a trench and concrete slab perimeter about 30 cm.
- 2.3 Then, drill holes in a trench by 50-60 cm depth and keep a distance between holes at 30 cm. Apply the finished dilution of ATM Anti-Termite SD with a rate of 6 litres per 1 metre of trench length.
- 2.4 Filling the soil back into the trench and apply the finished dilution one more at the rate of 6 litres/ metre. Finally, apply this treatment at ground level on the area which closed to concrete slab by using a finished dilution 3 litres/ metre.

### 3. For areas around the buildings, Lawns.

Ground treatment for Termites and Pests infestation can be done by using the finished dilution of ATM Anti-Termite SD to apply by a rate of 1-2 litres/ sq.m.

Tel: +66 2 312 1049-50, +66 2 750 4808-9 Fax: +66 2 312 1163

www.urpaints.com



# ATM Anti-Termite SD

Version 1.1

Date of issue 22/03/2021

	Date 01 Issue 22/03/2021
Storage & Shelf life	- Shelf life is 4 years in sealed container.
	- Keep away from open flames or other ignition sources.
	- Keep container in a cool and well-ventilated place. Avoid from direct sunlight.
	- Keep container tightly closed. Keep away from children, pets and foods.
	- Partly used container (concentrated) may be resealed and used again after correct
	storage.
Safety, Health and Environment	- DO NOT use ATM Anti-Termite SD for Agricultures.
Information	- DO NOT apply this treatment to the patient or infant's rooms.
	- Always wear the Protective Personal Equipment (PPE) to avoid the chemical contact
	with skin or eyes.
	- Isolate the treated area and deny entry to unnecessary or unprotected personnel
	and pets until the treatment will be finished completely.
	- Stay upwind when apply the treatment.
	- Do not breathe fume/ mist/ vapours/ spray.
	- Do not eat, drink or smoke when using this product.
	- Check for leaks after application. When leaks are observed, DO NOT allow people
	or pets to contact on contaminated areas until the cleaning is completed.
	- Remove PPE immediately after handling this product. Wash outside of gloves before
	removing. PPE including to the contaminated clothing should be washing before
	reuse.
	- Wash hands and body thoroughly after handling with soap and water.
	- DO NOT contaminate to public or private water supplies by cleaning equipments or
	disposal of wastes.
	- Avoid release to the environment, toxic to the aquatic life with long lasting effects.
	- DO NOT reuse or refill the container, it should be disposed by the local regulations.
Packing	250 ml. / 500 ml./ 1 Litre / 5 Litres

Bangkok 10120. Tel: +66 2 312 1049-50, +66 2 750 4808-9 Fax: +66 2 312 1163 www.urpaints.com