URAI PAINTS

www.urpaints.com

Technical Data Sheet

LOBSTER Shield Mold Wash - L715

Version 1.1

Date of issue 10.03.2021

Description

LOBSTER Shield Mold Wash – L715 is disinfecting solution for application on the infested surfaces such as masonry, wood, sandstone, etc. It provides a deep penetrated efficacy against bacteria, mold, fungi or algae. It is not affected to the subsequent coating.

Application

For treatment of mold infested area before repainting, both interior and exterior.

Technical Data

Product type	:	Biocide solution
Appearance	:	Clear colour liquid
Viscosity (ford cup #4)	:	8-11 seconds at 25 °C
Specific gravity (water=1)	:	0.900-1.000
pH	:	5 - 9
Dilution	:	Ready to use
Application	:	Brush/ Roller/ Spray gun
Drying time at 25 °C	:	At least 24 hours

Coating System

Surface preparation

Thoroughly clean surface to be painted with water. Make sure surface is free from dirt, dust, wax or grease and loose contaminants.

Instruction

- Using LOBSTER Shield Mold Wash – L715 to remove mold or fungus from surfaces. Apply by brush or spray gun on the infested surface.
- Leaves surface for 24 hours after treatment.
- Rinses with clean water and allow to dry.

Coverage

10–20 sq.m /litre/coat

Storage & Shelf life

Maximum 3 years in sealed container.

Keep container under an ambient temperature. When not in use, keep container tightly closed and use again after correct storage.

Packing

1 litre, 3.5 litres.

DISCLAIMER: *The above information provided herein is based on the present state of our knowledge and practical experience. Since the product is often used under different conditions beyond our control. We cannot guarantee anything but the quality of the product itself. All the rights are reserved to change the data without any notice.*

Sales office: 52, 54 Soi Sathorn 11 (Sect. 3) South Sathorn rd., Yannawaa, Sathorn, Bangkok 10120. Tel: +66 2 312 1049-50, +66 2 750 4808-9 Fax: +66 2 312 1163