

ATM Acrylic Sealant

Version 1.0

Date of issue 26/02/2021

Description	ATM acrylic sealant is a high-quality adhesive in a ready-to-use product.		
	Good for sealing gaps and joints. It provides smooth finish with flexible. Fast drying.		
	Excellent adhesion performance on different materials.		
Application	An ideal for caulking, grouting, jointing or sealing between door/ window frames.		
	Compatible with a variety of substrates e.g. concrete, wood, brick, ceramic, etc.		
	Exterior and interior use.		
Technical Data	Product type	:	Acrylic adhesive
	Appearance	:	White colour paste
	Viscosity	:	250,000 – 300,000 cps at 25°C
	Specific gravity (water=1)	:	1.400 – 1.600 at 25°C
	pH	:	8-10
	Drying time at 25 °C	:	Dry to touch 1 hr.
			Dry to scrub 2 hr.
			Dry to recoat 24 hr.
Application Instruction	Surface Preparation		
	Surface should be clean from dust, oil or grease, coating stains and all loose particles which may impact to surface adhesion.		
	Application		
	- Cut of nozzle tip and cartridge to the desired width. - Apply on surface by sealing with steady flow into gaps or joints, then wipe it to clean and smooth finish. - Allow it to dry (Avoid apply on high humidity condition.) - Top coat should be applied after 24 hours left.		
	Recommendation		
	- Do not apply to hot surface. Protect area from strong sunlight to avoid cracking or any deteriorated by rapid water evaporation. - Avoid applying during rain or humidity condition.		
Coverage	100 ml / 1 m (1 cm width and 1 cm depth)		

ATM Acrylic Sealant

Version 1.0

Date of issue 26/02/2021

Storage & Shelf life	Maximum 3 years in sealed container. Store in room temperature. Avoid UV exposure. Keep container tightly closed and keep it in a well-ventilated place.
Safety, Health and Environment Information	• Keep out of reach of children. • Use in a well-ventilated area. • If on skin, wash with plenty of soap and rinse skin with clean water. • If in eyes, rinse cautiously with water for several minutes. • Avoid release to the environment.
Packing	400 g