Technical Data Sheet

LOBSTERcrete Bonding Agent No.751

www.uraipaints.com

Version 1.0

Date of issue 26.02.2021

Description

LOBSTERcrete bonding agent no.751 is a superior quality of bonding agent for concrete and cement admixture. It helps to increase the strength and durability. Good chemical resistance. Excellent adhesion enhancement. High performance to improve bonding of new and old concrete surfaces.

Application

Suitable to be used for bricklaying mortars, rendering mortars and flooring concrete.

Technical Data

Product type	:	Concrete Admixtures
Appearance	:	Liquid in milky-white colour
Viscosity	:	55-60 KU at 25 °C
Specific Gravity (water = 1)	:	0.900–1.200 at 25 °C
pH	:	7-12

Application

Surface preparation

The surface should be clean and dry. Oil or waxy contamination must be cleaned off. It must be thoroughly wetted down before application.

Application

- For bonding of new and old concrete surfaces ceramic tiles, marbles.

  Lobster Crete bonding agent no.751: water = 1:1 (A), Cement: sand = 1:1 (B). Then, mix A with B until it is homogeneous.

- For skim rendering

  Lobster Crete bonding agent no.751: water = 1:1 (A), Cement: sand = 1:3 (B). Then, mix A with B until it is homogeneous.

Recommendation

- Shake well before use to get the best result.
- Pot life is 45 minutes after mixed.
- Curing the applied surface immediately with water or LOBSTER curing compound is strongly recommended to prevent any damage from cracking on concrete surface.

Coverage

1 litre will cover an area 4-5 sq.m with dry film thickness 1 mm.

DISCLAIMER: *The above information provided herein is based on the present state of our knowledge and practical experience. Since the product is often used under different conditions beyond our control. We cannot guarantee anything but the quality of the product itself. All the rights are reserved to change the data without any notice.*

Sales office: 16/8 Soi Sathorn 11 (Sect. 3) South Sathorn rd., Yannawa, Sathorn, Bangkok 10120. Sale Bangkok TEL: (+662) 312-1050 FAX: (+662) 312-1163
Sale Other Areas TEL: (+662) 312-1651 FAX: 312-1167

LOBSTERcrete Bonding Agent No.751

www.uraipaints.com

Version 1.0

Date of issue 26.02.2021

Storage & Shelf life	Best before 2 years in sealed container. Keep container in a cool dry and well-ventilated place. Protect from direct sunlight. When not in use, keep container tightly closed and use again after correct storage.
Safety, Health and Environment Information	• Keep out of reach of children. • Use in a well-ventilated area. • If on skin, wash with plenty of soap and rinse skin with clean water. • If in eyes, rinse cautiously with water for several minutes. • Avoid release to the environment.
Packing	1 Litre, 5 Litres and 20 Litres.

DISCLAIMER: *The above information provided herein is based on the present state of our knowledge and practical experience. Since the product is often used under different conditions beyond our control. We cannot guarantee anything but the quality of the product itself. All the rights are reserved to change the data without any notice.*

Sales office: 16/8 Soi Sathorn 11 (Sect. 3) South Sathorn rd., Yannawa, Sathorn, Bangkok 10120. Sale Bangkok TEL: (+662) 312-1050 FAX: (+662) 312-1163
Sale Other Areas TEL: (+662) 312-1651 FAX: 312-1167