

ATM Spray Gold Paint

www.urapaints.com

No. C981, C982, C988 and C989

Date of issue 26.04.2022 Version 1.0

Description	<p>ATM spray gold paint is specially formulated from a synthetic resin and high quality of gold pigment. It provides smooth and shiny gold finish. Quick drying and excellent adhesion. Good quality of nozzle to deliver a beautiful colour and texture.</p>																					
Application	<p>It is suitable for creation art works or repairable parts on any kinds of substrate such as wood, plastic or metal substrate.</p>																					
Technical Data	<table> <tr> <td>Product type</td> <td>:</td> <td>Petroleum Resin</td> </tr> <tr> <td>Appearance</td> <td>:</td> <td>Colour liquid spray regarding to catalog.</td> </tr> <tr> <td>Film type</td> <td>:</td> <td>Gloss</td> </tr> <tr> <td>Viscosity (Ford cup # 4)</td> <td>:</td> <td>12-14 sec at 25 °C (In liquid state)</td> </tr> <tr> <td>Flash point</td> <td>:</td> <td>-73 °C (Based on the lowest flash point material, spray propellant (LPG – Liquefied Petroleum Gas))</td> </tr> <tr> <td>Air vapour pressure</td> <td>:</td> <td>4.5 – 5 kg/cm² at 30 °C</td> </tr> <tr> <td>Drying time</td> <td>:</td> <td>- Dry to touch 15 minutes - Dry to recoat 1 hour</td> </tr> </table>	Product type	:	Petroleum Resin	Appearance	:	Colour liquid spray regarding to catalog.	Film type	:	Gloss	Viscosity (Ford cup # 4)	:	12-14 sec at 25 °C (In liquid state)	Flash point	:	-73 °C (Based on the lowest flash point material, spray propellant (LPG – Liquefied Petroleum Gas))	Air vapour pressure	:	4.5 – 5 kg/cm ² at 30 °C	Drying time	:	- Dry to touch 15 minutes - Dry to recoat 1 hour
Product type	:	Petroleum Resin																				
Appearance	:	Colour liquid spray regarding to catalog.																				
Film type	:	Gloss																				
Viscosity (Ford cup # 4)	:	12-14 sec at 25 °C (In liquid state)																				
Flash point	:	-73 °C (Based on the lowest flash point material, spray propellant (LPG – Liquefied Petroleum Gas))																				
Air vapour pressure	:	4.5 – 5 kg/cm ² at 30 °C																				
Drying time	:	- Dry to touch 15 minutes - Dry to recoat 1 hour																				
Application Instruction	<p>Surface Preparation</p> <p>The surface should be clean and dry. If there are oil or waxy contaminate must be cleaned off before coating.</p> <p>Coating</p> <ul style="list-style-type: none"> - Shake well for 2 minutes before use and shake periodically during spray. - Keep distance about 1 foot. - For better result apply several thin coatings with an interval of 10-15 minutes. - After finish, tum canister upside down and press for a while to clean the spray nozzle. <p>Recommendation</p> <ul style="list-style-type: none"> - Interior use only. - No primer is needed. - Avoid top coating with lacquer or colour spray to prevent any damage from bleeding. 																					
Coverage	<p>3 - 4.5 sq.m / coat / can (226 g)</p>																					
Storage & Shelf life	<p>Best before 2 years in sealed container. Protect from sunlight. Do not expose to temperatures exceeding 25-30 °C. Keep it in a well-ventilated place.</p>																					

DISCLAIMER: The above information provided herein is based on the present state of our knowledge and practical experience. Since the product is often used under different conditions beyond our control. We cannot guarantee anything but the quality of the product itself. All the rights are reserved to change the data without any notice.

Sales office: 16/8 Soi Sathorn 11 (Sect. 3)
 South Sathorn rd., Yannawa, Sathorn,
 Bangkok 10120.
 Tel: +66 2 312 1049-50, +66 2 750 4808-9
 Fax: +66 2 312 1163
www.urapaints.com

ATM Spray Gold Paint

www.uraipaints.com

No. C981, C982, C988 and C989

Date of issue 26.04.2022 Version 1.0

Safety, Health and Environment Information	<ul style="list-style-type: none">● Keep out of reach of children.● Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.● Use in a well-ventilated area.● Do not spray on an open flame or other ignition source.● If on skin, wash with plenty of soap and rinse skin with clean water.● If in eyes, rinse cautiously with water for several minutes.● Do not pierce or burn, even after use.● Avoid release to the environment.
Packing	226 g

Remark: This data use for ATM Spray gold paint No. C981, C982, C988 and C989

DISCLAIMER: The above information provided herein is based on the present state of our knowledge and practical experience. Since the product is often used under different conditions beyond our control. We cannot guarantee anything but the quality of the product itself. All the rights are reserved to change the data without any notice.

Sales office: 16/8 Soi Sathorn 11 (Sect. 3)
South Sathorn rd., Yannawa, Sathorn,
Bangkok 10120.
Tel: +66 2 312 1049-50, +66 2 750 4808-9
Fax: +66 2 312 1163
www.uraipaints.com

ATM Spray Gold Paint

www.uraipaints.com

No. C983

Date of issue 26.02.2022 Version 1.0

Description	<p>ATM spray gold paint no. C983 is specially formulated from a synthetic resin and high quality of gold pigment. It provides smooth and matt gold finish. Quick drying and excellent adhesion. Good quality of nozzle to delivers a beautiful colour and texture.</p>																					
Application	<p>It is suitable for creation art works or repairable parts on any kinds of substrate such as wood, plastic or metal substrate.</p>																					
Technical Data	<table border="0"> <tr> <td>Product type</td> <td>:</td> <td>Acrylic Resin</td> </tr> <tr> <td>Appearance</td> <td>:</td> <td>Colour liquid spray regarding to catalog.</td> </tr> <tr> <td>Film type</td> <td>:</td> <td>Matt</td> </tr> <tr> <td>Viscosity (Ford cup # 4)</td> <td>:</td> <td>12-14 sec at 25 °C (In liquid state)</td> </tr> <tr> <td>Flash point</td> <td>:</td> <td>-73 °C (Based on the lowest flash point material, spray propellant (LPG – Liquefied Petroleum Gas))</td> </tr> <tr> <td>Air vapour pressure</td> <td>:</td> <td>4.5 – 5 kg/cm² at 30 °C</td> </tr> <tr> <td>Drying time</td> <td>:</td> <td>- Dry to touch 15 minutes - Dry to recoat 1 hour</td> </tr> </table>	Product type	:	Acrylic Resin	Appearance	:	Colour liquid spray regarding to catalog.	Film type	:	Matt	Viscosity (Ford cup # 4)	:	12-14 sec at 25 °C (In liquid state)	Flash point	:	-73 °C (Based on the lowest flash point material, spray propellant (LPG – Liquefied Petroleum Gas))	Air vapour pressure	:	4.5 – 5 kg/cm ² at 30 °C	Drying time	:	- Dry to touch 15 minutes - Dry to recoat 1 hour
Product type	:	Acrylic Resin																				
Appearance	:	Colour liquid spray regarding to catalog.																				
Film type	:	Matt																				
Viscosity (Ford cup # 4)	:	12-14 sec at 25 °C (In liquid state)																				
Flash point	:	-73 °C (Based on the lowest flash point material, spray propellant (LPG – Liquefied Petroleum Gas))																				
Air vapour pressure	:	4.5 – 5 kg/cm ² at 30 °C																				
Drying time	:	- Dry to touch 15 minutes - Dry to recoat 1 hour																				
Application Instruction	<p>Surface Preparation</p> <p>The surface should be clean and dry. If there are oil or waxy contaminate must be cleaned off before priming.</p> <p>Priming</p> <p>Priming by ATM spray acrylic primer yellow No. A 118 for 2 coats. Drying time to recoat 15 minutes by approximately.</p> <p>Coating</p> <ul style="list-style-type: none"> - Shake well for 2 minutes before use and shake periodically during spray. - Keep distance about 1 foot. - For better result apply several thin coatings with an interval of 10-15 minutes. - After finish, tum canister upside down and press for a while to clean the spray nozzle. <p>Recommendation</p> <p>If you want gloss finish, you can apply ATM spray acrylic clear top coat No. A 031 as last step to get a shiny and sparkling film.</p>																					
Coverage	<p>3 – 4.5 sq.m / coat / can (226g)</p>																					

ATM Spray Gold Paint

www.uraipaints.com

No. C983

Date of issue 26.04.2022 Version 1.0

Storage & Shelf life	Best before 2 years in sealed container. Protect from sunlight. Do not expose to temperatures exceeding 25-30 °C. Keep it in a well-ventilated place.
Safety, Health and Environment Information	<ul style="list-style-type: none">● Keep out of reach of children.● Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.● Use in a well-ventilated area.● Do not spray on an open flame or other ignition source.● If on skin, wash with plenty of soap and rinse skin with clean water.● If in eyes, rinse cautiously with water for several minutes.● Do not pierce or burn, even after use.● Avoid release to the environment.
Packing	226 g

DISCLAIMER: The above information provided herein is based on the present state of our knowledge and practical experience. Since the product is often used under different conditions beyond our control. We cannot guarantee anything but the quality of the product itself. All the rights are reserved to change the data without any notice.

Sales office: 16/8 Soi Sathorn 11 (Sect. 3)
South Sathorn rd., Yannawa, Sathorn,
Bangkok 10120.
Tel: +66 2 312 1049-50, +66 2 750 4808-9
Fax: +66 2 312 1163
www.uraipaints.com